

Data sheet Product LA_V_HPK2_




Cooling aggregates > Cooling aggregates with axial fan

- cooling aggregates of special conception with pressed in fins
- enlarged surface by means of fluted fin geometry
- flow-optimised hollow fin structure
- milled flat mounting surface for component assembly
- maximum heatsink length 300 mm
- special designs and other fans upon request

Features

width:	330 mm
height:	90 mm
length:	100 mm / 150 mm / 200 mm / 250 mm / 300 mm
thermal resistance:	0.034 - 0.07 K/W
surface:	raw degreased aluminium
operating voltage of the fan motor:	<ul style="list-style-type: none"> • 12 V DC • 24 V DC • 48 V DC

Technical Drawing



Fan**ebmpapst 8212 JH4, 12 V DC**

type:	ebmpapst 8212 JH4
dimensions:	80x80x38 mm
tension:	12 V DC
power inout:	39 W
max. air volume:	222 m ³ /h
temperature range:	-20°C... +70°C
speed:	14,000 min ⁻¹
noise level:	71 dB(A)
weight:	200 g
failure rate (L ₁₀):	L ₁₀ > 50,000 h (40°C)

ebmpapst 8214 JH4, 24 V DC

type:	ebmpapst 8214 JH4
dimensions:	80x80x38 mm
tension:	24 V DC
power inout:	38 W
max. air volume:	222 m ³ /h
temperature range:	-20°C... +70°C
speed:	14,000 min ⁻¹
noise level:	71 dB(A)
weight:	200 g
failure rate (L ₁₀):	L ₁₀ > 50,000 h (40°C)

ebmpapst 8218 JH4, 48 V DC

type:	ebmpapst 8218 JH4
dimensions:	80x80x38 mm
tension:	48 V DC
power inout:	36 W
max. air volume:	222 m ³ /h
temperature range:	-20°C... +70°C
speed:	14,000 min ⁻¹
noise level:	71 dB(A)

weight:

200 gfailure rate (L₁₀):**L₁₀ > 50,000 h (40°C)****Fischer Elektronik GmbH & Co. KG**
DEUTSCHLAND • GERMANY • ALLEMAGNENottebohmstraße 28
58511 LüdenscheidTelefon +49 2351 435-0
Telefax +49 2351 45754info@fischerelektronik.de
www.fischerelektronik.de